

**VLIW COMPUTER PROCESSING ARCHITECTURE HAVING A SCALABLE
NUMBER OF REGISTER FILES****ABSTRACT OF THE DISCLOSURE**

According to the invention, a processing core (12) comprising one or more
5 processing pipelines (100) having N-number of processing paths (56), each of which process
instructions (54) on M-bit data words. In addition, the processing core (12) includes a
plurality of register files (60), each preferably having Q-number of registers which are M-
bits wide. Preferably, every two of the processing paths (56) share one register file (60). A
processing instruction (52) preferably comprises N-number of P-bit instructions (54)
10 appended together to form a very long instruction word (VLIW), and the N-number of
processing paths (56) preferably process the N-number of P-bit instructions (54) in parallel.
In accordance with one preferred embodiment of the invention, M is 64, Q is 64 and P is 32.
Accordingly, the N-number of processing paths (56), each process 32-bit instructions (54) on
64-bit data words, and the plurality of register files (60) each have 64 registers which are 64-
15 bits wide. Processing pipeline (100) preferably comprises a fetch stage (110), a decode stage
(120), an execute stage (130) and a write-back stage (140). The execute stage (130)
preferably comprises an execute unit (134) for each of the N-number of processing paths
(56). Each execute unit (134) includes an integer processing unit (64), a load/store
processing unit (66), a floating point processing unit (68), or any combination of one or more
20 of those units. Unlike prior art processor designs, an integer processing unit (64) and a
floating point processing unit (68) in one or more of the execute units (134) share a single
register file (60).

DE 7034251 v1

25